

DRILLS & ROTARY HAMMERS



SDS Plus 3 Mode Hammer



KHE 3251

- 3 x mode- Rotary hammer, drilling, chiselling
- Marathon motor: More torque, More power output, Higher overload capacity, Maximum durability
- Metabo S-automatic safety clutch
- Metabo Quick: quick change between SDS Plus hammer chuck and keyless chuck for drilling in wood and metal
- Metabo VibraTech (MVT): integrated damping system and side handle
- High performance hammer action
- Ergonomic housing shape for chiselling tasks without side handle
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- High performance hammer action
- Cable-protecting ball joint for optimal freedom of motion when working

Rated input	800 w
Drill ø	st / wd / conc. 13 / 35 / 32 mm
Speed	0-1,150 rpm
Impact rate	4,470 bpm
Impact energy	3.1 j
Weight	3.6 kg



BONUS
Includes: Chuck 31968



The Metabo 3-year warranty
We give you an extra long 3 year warranty on all our products. Simply register up to 4 weeks after your purchase on the Internet and your regular guarantee is extended to three years.
Register at www.metabo.com/xxl

metabo®

PROFESSIONAL POWER TOOL SOLUTIONS

3 Mode SDS Plus



KHE 2644

- 3 x mode- Rotary hammer, drilling, chiselling
- Metabo S-automatic safety clutch
- High performance hammer action
- Hammer stop for drilling in rotary only mode
- Rotation stop for chiselling
- Clockwise and anti-clockwise rotation
- Electronic soft start
- Vario (V)-electronics-variable speed

Rated input	800 w
Drill ø	St / wd / conc. 13 / 30 / 26 mm
Speed	0-1,150 rpm
Impact rate	5,400 bpm
Impact energy	2.3 j
Weight	2.9 kg



2 Mode SDS Max Hammers



KHE 5-40

- Metabo S-automatic safety clutch
- VTC Electronics: Constant torque even under load, Variable Speed
- Brush wear display
- Auto stop carbon brushes
- Rotation stop
- Vibration damping system
- Magnesium die-cast gear housing



KHE 56

- Metabo S-automatic safety clutch
- VTC Electronics: Constant torque even under load, Variable Speed
- Brush wear display
- Auto stop carbon brushes
- Rotation stop
- Vibration damping system
- Magnesium die-cast gear housing



KHE 96

- Metabo S-automatic safety clutch
- VTC Electronics: Constant torque even under load, Variable Speed
- Brush wear display
- Auto stop carbon brushes
- Rotation stop
- Vibration damping system
- Magnesium die-cast gear housing

SDS Max Demolition Hammers



MHE 5

- VTC Electronics: Constant torque even under load, Variable Speed
- Brush wear display
- Auto stop carbon brushes
- Rotation stop
- Vibration damping system
- Magnesium die-cast gear housing



MHE 96

- VTC Electronics: Constant torque even under load, Variable Speed
- Brush wear display
- Auto stop carbon brushes
- Rotation stop
- Vibration damping system
- Magnesium die-cast gear housing

Technical Data	KHE 5-40	KHE 56	KHE 96	MHE 5	MHE 96
Rated input	1,010 w	1,300 w	1,700 w	1,300 w	1,600 w
Type	SDS Max 40 mm	SDS Max 45 mm	SDS Max 50 mm	SDS Max	SDS Max
Max. Impact rate	3,200 bpm	2,840 bpm	1,950 bpm	3,000 bpm	1,950 bpm
Impact energy	75 j	8.5 j	20 j	8.6 j	20 j
Torque	95 Nm	90 Nm	120 Nm	NA	NA
Weight	6.2 kg	6.7 kg	11.8 kg	6.6 kg	11 kg

High Torque Drills



BE 75-16

- Robust die cast aluminium gear housing
- Rotating carbon brush bridge e.g. for the removal of stubborn screws
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo S-automatic safety clutch
- Spindle with hexagonal recess for screwdriver bits for working without chuck



BDE 1100

- Metabo S-automatic safety clutch
- High Torque
- Forward & Reverse
- Alloy 2 x speed gearbox
- 16mm metal keyed chuck
- Auto Stop Carbon Brushes

Technical Data	BE 75-16	BDE 1100
Rated input	750 w	1,100 w
Torque	75 Nm	55 / 22 Nm
Speed	0-660 /min	0-640 / 0-1200 /min
Max. Drill Capacity ø	steel / wood 16 / 50 mm	steel / wood 16 / 40mm
Weight	2.5 kg	3.8 kg

NEW Impact Drills



SBE 850-2

- Marathon motoR
- Metabo S-automatic safety clutch
- Variable Speed
- Alloy 2 x speed gearbox
- Auto Stop Carbon Brushes
- 13mm metal keyless chuck



NEW



SBEV 1000-2

- Marathon motor
- Metabo S-automatic safety clutch
- VTC Electronics: Constant torque even under load, Variable Speed
- Alloy 2 x speed gearbox
- Auto Stop Carbon Brushes
- 13mm metal keyless chuck



SBEV 1100-2 S

- Marathon motor
- Metabo S-automatic safety clutch
- VTC Electronics
- Overload protection
- Soft Start & Restart protection
- Impulse Mode
- Auto-stop carbon brushes
- 13mm metal keyless chuck



SBEV 1300-2 S

- Marathon motor
- Metabo S-automatic safety clutch
- VTC Electronics
- Overload protection
- Soft Start & Restart protection
- Impulse Mode
- Auto-stop carbon brushes
- 13mm metal keyless chuck

Technical Data	SBE 850-2	SBEV 1000-2	SBEV 1100-2 S	SBEV 1300-2 S
Rated input	850 w	1010 w	1,100 w	1,300 w
Max. Torque	14 / 36 Nm	14 / 40 Nm	15 / 42 Nm	16 / 44 Nm
Impact rate	58,900 bpm	53,200 bpm	58,900 bpm	58,900 bpm
Speed	0-1100 / 0-3100 rpm	0-1000 / 0-2800 rpm	0-1100 / 0-3100 rpm	0-1100 / 0-3100 rpm
Max. Drill Capacity ø	steel / wood / conc. 13 / 40 / 18 mm	steel / wood / conc. 16 / 40 / 20 mm	steel / wood / conc. 16 / 40 / 22mm	steel / wood / conc. 16 / 40 / 22mm
Weight	2.6 kg	2.7 kg	2.8 kg	2.8 kg

THE METABO SAFETY & PERFORMANCE ADVANTAGE

MARATHON MOTOR
Higher overload capacity for more efficiency

S-AUTOMATIC SAFETY CLUTCH
Mechanical clutch Prevents Kickback

VTC ELECTRONICS VARIABLE SPEED
Thumb wheel for customisable speed.

ANTI-VIBRATION SIDE HANDLE
Reduces hand-arm vibrations

QUICK CHANGE
ChuckTool free chuck change

SOFT START
Greater initial control at start up

M+ Fully Intergrated Dust Extraction System



35 Litre Vacuums with Auto Clean

ASR 35 L ACP

ASR 35 M ACP

- Auto filter cleaning mode
- Auto Trailing:
- 2 Strong/Washable M-class:
- Power socket with auto start
- Automatic shut-off: when liquid reaches the drum capacity
- Soft Start
- M Class model includes Anti Static hose



ASA 32 L

- Socket with Auto start



Technical Data	ASA 32 L	ASR 35 L ACP	ASR 35 M ACP
Rated input	1,200 w	1,400 w	1,400 w
Vacuum	200 hpa (mbar)	248 hpa (mbar)	248 hpa (mbar)
Filter surface	3,600 cm ²	8.600 cm ²	8.600 cm ²
Hose	3.2 m x ø 35 mm	3.2 m x ø 35 mm	3.2 m x ø 35 mm
Container volume	32 litres	35 litres	35 litres



Dust extraction adaptor for drills

630829000

- Dust free drilling!



For unrivalled destructive force check out Metabo's huge range of SDS Plus and Max bits and accessories at:



The Metabo 3-year warranty

We give you an extra long 3 year warranty on all our products. Simply register up to 4 weeks after your purchase on the Internet and your regular guarantee is extended to three years. Register at www.metabo.com/xxl

metabo®

PROFESSIONAL POWER TOOL SOLUTIONS

Metabo Pty Ltd ABN 80 004 697 741
 10 Dalmore Drive Scoresby 3179
 P (03) 9765 0199 F (03) 9765 0189
 1800 METABO
sales@metabo.com.au
www.metabo.com.au

METABO RESERVES THE RIGHT TO CORRECT ANY PRINTED ERRORS.(E&OE). PRODUCTS MAY VARY DUE TO TECHNICAL CHANGES & AVAILABILITY. AUGUST 2017